



Product Information

- Applications:** Cove, Linear, Accent, Decorative
- Volts:** 24V
- Lamps:** Incandescent .9W or 1.8W
- Lamp Life:** See Lamp Specifications
- Socket:** Clear Custom
- Extrusion:** Gold Extrusion

Indoor & Outdoor Applications

- Amusement Industries**
Night Clubs, Movie Theatres
- Recreation Industries**
Hotels, Restaurants, Casinos
- Architectural Industries**
Interior Decor, Shopping Centers
- Construction Industries**

Lamp Specifications

Catalog #	Description	Volts	Watts	Lamp Life Hrs.	Max. Lamps Per Run	3" O/C	6" O/C	12" O/C	18" O/C
.9W	.9 Watt Incandescent	24	4.5	30,000	213	53'	106'	213'	319'
1.8W	1.8 Watt Incandescent	24	5.4	30,000	106	26'	53'	106'	59'

Specifier: _____

Product Code: **Series /Lamp/Volts/Cap/Lens/Spacing/Wet-Dry**
 EL9000/ / 24V / / / / /

Project: _____

Type: _____

Date: _____

* Note: in cap area write WNC if you do not want a cap on lamp. WCC for a clear cap. You can not choose lens if you have a cap. Write NLE for no lens. If you want the optional lens cover write WLE. If you want a clear lens you must choose WNC(with no cap) for cap.

Application and Construction

Designed to utilize a gold extrusion. ExtruLite provides many desirable features. Of primary importance the option of incandescent lamps with a long lamp life. The gold extrusion helps protect the system from harsh weather and damage to the wiring. Easy lamp replacement makes an excellent product to reduce maintenance in the future.

ExtruLite is mounted easily by first mounting the base of the gold extrusion and then snapping together the top part. ExtruLite is shipped in 8' section for field cutting if necessary. Thus not requiring exact field dimensions.

ExtruLite is excellent to illuminate areas in casinos, hotels, retail shops, restaurants, etc. Suggested spacing is 6" on center.

Electrical

ExtruLite is supplied with a 120V (primary side)/24V (secondary side) transformer. Specify other primary side voltage if different than 120V. FestLite runs at 24V. ExtruLite is an 8 amp system (18 gage wire).

Optional Accessories

Lens cover for gold extrusion.