


Drawing # LPL8700



Fixture Type

Product Features

- Applications:** Accent, Decorative Ltg.
- Voltage:** 12V
- Lamp Type:** LEDs or Incandescent
- Socket:** Custom
- Length:** Built to Order
- Construction:** White PVC Extrusion
- Wiring:** Parallel
- Mounting:** Screws or Clips
- Listing:** Dry Location

Applications

Designed for indoor use, LipLite Series is ideal for many applications including the amusement, recreation, and architectural industries. LipLite is excellent for decorative lighting, accent lighting, path lighting, and many more applications.

LipLite is used in:

- Restaurants
- Casinos
- Retail Stores/Shopping Malls
- Hotels
- Movie Theatres and many more

Electrical

LipLite is a 12 Volt system. LipLite requires a 12V (secondary side) transformer. The standard primary side voltage on our transformers is 120V or 277V. Consult factory for other primary side voltages. A thermal breaker box can be used for secondary protection. See Transformer Brochure.

How to Order or Specify

Product Code: (Fill in the Blanks)

LPL8700 / _____ / _____ / _____ / _____

Ex: LPL8700	12"	LED-2.7K	CL	Dry
Series	Spacing	Lamp	Lens	Dry or Wet
LPL8700	3/4" O/C	LED-2.7K	Clear (CL)	Dry (Indoor)
	1" O/C	LED-3.0K	Frosted (FL)	Wet (Outdoor)
	1.5" O/C	LED-3.5K		
	2" O/C	LED-4.0K		
	3" O/C	LED-4.5K		
	4" O/C	LED-5.0K		
	6" O/C	LED-5.7K		
	8" O/C	LED-6.5K		
	12" O/C			

Lamp Specifications

Lamp #	Description	Lamp Life	Watts	Max. Lamps	1.5" O/C	2" O/C	3" O/C	4" O/C	6" O/C	8" O/C	12" O/C
LED-2.7K	2700K Warm White	50,000 hrs.	.25	200	25'	33'	50'	66'	100'	133'	200'
LED-3.0K	3000K Warm White	50,000 hrs.	.25	200	25'	33'	50'	66'	100'	133'	200'
LED-3.5K	3500K Neutral White	50,000 hrs.	.25	200	25'	33'	50'	66'	100'	133'	200'
LED-4.0K	4000K Neutral White	50,000 hrs.	.25	200	25'	33'	50'	66'	100'	133'	200'
LED-4.5K	4500K Neutral White	50,000 hrs.	.25	200	25'	33'	50'	66'	100'	133'	200'
LED-5.0K	5000K Cool White	50,000 hrs.	.25	200	25'	33'	50'	66'	100'	133'	200'
LED-5.7K	5700K Cool White	50,000 hrs.	.25	200	25'	33'	50'	66'	100'	133'	200'
LED-6.5K	6500K Cool White	50,000 hrs.	.25	200	25'	33'	50'	66'	100'	133'	200'

Date:		Specifier:		Project:	
-------	--	------------	--	----------	--



2034 E. Lincoln Ave. # 431 • Anaheim, CA 92806
 TF: 800.921.CALI (2254) • PH: 714-535-7900 • FX: 714.535.7902
 Web site: www.calilighting.com • E-mail: info@calilighting.com

