



Lamp Specifications

Catalog #	Description	Volts	Watts	Lamp Life Hrs.	Max. Lamps Per Run	3" O/C	6" O/C	12" O/C	18" O/C
.9W	.9 Watt Incandescent	24	4.5	30,000	213	53'	106'	213'	319'
1.8W	1.8 Watt Incandescent	24	5.4	30,000	106	26'	53'	106'	59'

Product Information

Applications: Accent, Linear, Decorative Lighting
Volts: 24V
Lamps: 0.9 W or 1.8W
Lamp Life: 30,000 Hrs.
Socket: Custom Green Socket
Wire Color: Green 18/2 Wire

Indoor or Outdoor Applications

- Amusement Industries**
Night Clubs, Movie Theatres
- Recreation Industries**
Hotels, Restaurants, Casinos
- Architectural Industries**
Interior Decor, Shopping Centers
- Construction Industries**

Specifier: _____

Product Code: **Series /Spacing/ Lamp**
 TRL3000/ _____ / _____

Project: _____

Type: _____

Date: _____

Application and Construction

Designed to utilize incandescent lamps, TreeLite 7500 Series provides many desirable features. Of primary importance is the parallel wiring. If one lamp goes out, only that lamp is not working. The rest of the lamps continue working. The long lamp life of incandescent lamps are excellent for the hard to reach places for future lamp replacement. A lens cap protects the lamps from harsh weather. Standard color is clear.

TreeLite has the option of being mounted with easy to install tie wraps. TreeLite can be easily field cut for an easy and fast installation not requiring exact field dimensions.

TreeLite is excellent to illuminate areas for decorative lighting. Green wire make TreeLite an excellent choice for tree branches, shrubs, palm trees, etc.

Suggested spacing is 12" for trees, shrubs, palm trees, etc. For a more sparkle effect 3" on center is excellent.

Electrical

TreeLite is supplied with a 120V (primary side)/24V (secondary side) transformer. Specify other primary side voltage if different than 120V. TreeLite runs at 24V. TreeLite is an 8 amp system (18 gage wire).

Accessories

TreeLite comes with a clear lens cover. Other colors available. Consult Factory. For mounting on branches use tie wraps.