



Lamp Specifications

| Catalog # | Description | Volts | Watts | Lamp Life Hrs. | Max. Lamps Per Run | 2" O/C | 3" O/C | 4" O/C | 6" O/C |
|-----------|------------------------|-------|-------|----------------|--------------------|--------|--------|--------|--------|
| 4W | 4 Watt Incandescent | 24 | 4.5 | 42,000 | 80 | 13' | 20' | 26' | 40' |
| 5W | 5 Watt Xenon | 24 | 5.4 | 10,000 | 66 | 11' | 16' | 22' | 33' |
| 7W | 7 Watt Xenon | 24 | 7.5 | 10,000 | 48 | 8' | 12' | 16' | 24' |
| 4WF | 4 Watt Incand. Frosted | 24 | 4.5 | 42,000 | 80 | 13' | 20' | 26' | 40' |
| 5WF | 5 Watt Xenon Frosted | 24 | 5.4 | 10,000 | 66 | 11' | 16' | 22' | 33' |
| 7WF | 7 Watt Xenon Frosted | 24 | 7.5 | 10,000 | 48 | 8' | 12' | 16' | 24' |

Product Information

Applications: Cove, Linear, Accent, Indirect Lighting
Volts: 24V (12V Available Upon Request)
Lamps: Wedge 4.5W, 5W or 7W (Included)
Lamp Life: See Lamp Specifications
Socket: Upright White Wedge Base
Optional: Lens Cover for V-Reflector

Indoor Applications

- Amusement Industries**
Night Clubs, Movie Theatres
- Recreation Industries**
Hotels, Restaurants, Casinos
- Architectural Industries**
Interior Decor, Shopping Centers
- Construction Industries**

Specifier: _____

Product Code: **Series /Spacing/ Lamp / Mounting**
 WL7000/ _____ / _____ / _____

Project: _____

Type: _____

Date: _____

Application and Construction

Designed to utilize upright wedge base lamps, WedgeLite 7000 Series provides many desirable features. Of primary importance the option of the long lamp life of incandescent lamps for a warm color. For a whiter color, xenon lamps are excellent. WedgeLite sockets are mounted in an upright position which makes the system easier for future lamp replacement, thus reducing maintenance costs.

WedgeLite has the option of being mounted with easy to install mounting clips, u-channel, or v-reflector. WedgeLite can be easily field cut for an easy and fast installation not requiring exact field dimensions.

WedgeLite is excellent to illuminate areas for cove or indirect lighting. The flexible wire is excellent for round or snake type coves..

Suggested spacing is 3"-4" for scallop free cove lighting.

Electrical

WedgeLite is supplied with a 120V (primary side)/24V (secondary side) transformer. Specify other primary side voltage if different than 120V. WedgeLite runs at 24V. WedgeLite is a 15 amp system (12 gage wire).

Optional Accessories

Lens cover for v-reflector

Also available for wet or outdoor applications.