# *lip*LEDs™ Color Tuning

**MODEL NUMBER** LLED**8300-HC**

**FIXTURE TYPE**

## FEATURES

| | |
|---|---|
| **APPLICATIONS** | Accent, Decorative Lighting |
| **VOLTAGE** | 24VDC |
| **LAMP TYPE** | Color Tuning LEDs |
| **DIMMING** | DMX-512 |
| **LENGTH** | Built to Order |
| **MOUNTING** | Pendant Mount |
| **VIEWING ANGLE** | 120 Degrees |
| **L70 LED LIFE** | 60,000 hrs. |
| **MAXIMUM RUN*1** (Based on 5 amps) | 26' (4.5W) |
| **LISTING** | Dry Location<br>UL2108, CSA C22.2#9<br>UL8750, CSA250 |

## ELECTRICAL

*lip*LEDs is a 24 Volt system that requires a 24VDC (secondary side) transformer. The standard primary side voltage on our transformers is 120V or 277V. Consult factory for other primary side voltages. See transformer brochure for additional information.

## DMX CONTROL SYSTEM (Not Included)




DMX-CT-5A DMX Decoder is required for DMX color tuning.
Set DMX address using DIP switches.
Compatible with DMX-512 1990 standard protocol. See DMX-CT-5A for details.

DMX-CT-128C or DMX-CT-1024C DMX Controller is capable of programming specific colors and scenes via software. See DMX-CT-128C or DMX-CT-1024C for details.

An electronic transformer must be used to operate the DMX control system.
See TRA-E brochure for details.

## ACCESSORIES (Not Included)

**Click on thumbnail of accessory to see cut sheet, if applicable**




**Power Connector**
(#LLED8300-PC)
Shrink tube included for Wet Locations

**DMX Decoder**
(#DMX-CT-5A)



**Electronic Transformer**
(#TRAXXX-E-UNV-24VDC-10V)
(XXX = Specify Wattage)

**DMX Signal Terminator**
(#DMX-RJ45-TERMINATOR)



**Standard Controller**
(#DMX-CT-128C)



**Color Wheel Controller**
(#DMX-CT-1024C)

## LAMP SPECIFICATIONS

| LAMP NUMBER | DESCRIPTION |
|---|---|
| LED-CT | 2400K-6400K Color Tuning |

NOT TO SCALE

± .015" tolerance




## MOUNTING OPTION (Not Included)

**Click on thumbnail of mounting clip to see cut sheet**




**Hanging Mounting Clip**
(#LLED8300-HC-MC-H)

## SPECIFY PRODUCT CODE (Use drop down menu to complete table or fill in the blanks)

LLED8300-HC - _____ - 4.5W - DMX - LED-CT - DRY - _____

| SERIES | OPTICS | WATTS PER FOOT | DIMMING | LAMP | LISTING | FINISH |
|---|---|---|---|---|---|---|
| *Ex. LLED8300-HC* | *F* | *4.5W* | *DMX* | *LED-CT* | *DRY* | *WH* |
| LLED8300-HC | Clear Lens (CL) | 4.5 Watts (4.5W) | DMX-512 (DMX) | 2400K-6400K Color Tuning (LED-CT) | Indoor (DRY) | Natural Silver (NA)*2 |
| | 50% Semi-Frosted Lens (SF) | | | | | Polished (PA) |
| | | | | | | White (WH) |
| | | | | | | Satin (SA) |
| | 100% Frosted Lens (F) | | | | | Black (BK) |
| | | | | | | Green (GN) |
| | | | | | | Red (RD) |
| | | | | | | Silver (SR) |

*1 Maximum run based on 4 amps for class II applications 21' (4.5W)
*2 Standard Finish: Natural Silver if left blank
*3 Run lengths required for Wet Location products (To ensure proper seal)

CALI
CALIFORNIA ACCENT LIGHTING, INC.
2034 E. Lincoln Ave. #431, Anaheim, CA 92806
ph. 800.921.CALI (2254) or 714.535-7900 \ fx. 714.535.7902
info@calilighting.com \ calilighting.com
© CALI. All rights reserved. CALI reserves the right to make changes or withdraw specifications without prior notice.

2018.11.09 R2