

#### Manufactured in the U.S.A.



"Lighting for the Professional Designer"

### PRODUCT Construction

Applications: Cove, Accent, Display, Undercounter, Undercabinet,

Soffit, Niche, Shelves, Backlighting, Cornice, and

Other Indirect Lighting

Voltage: 12VDC LEDs, 12VAC Incandescent

Sockets: Custom Sockets

Lamps: Replaceable LEDs (50,000Hrs Lamp Life)

and Incandescent Lamps

Spacing: 3/4", 1", 1.5", 2", 3", 4", 6", 12", or other Custom Spacing

Length: Built To Order (Custom Lengths to Fit Application)
Lead Wire: Standard 1' Lengths (Custom Lengths Available)
Mounting: Surface Mount with Mounting Clips or Channels

Options: U-Channels, V-Reflectors, Tubes

Dimming: Full Range Dimming Available (Consult Factory)
Binning: Tight Binning to Specified Color Temperature (+/-50k)
Testing: LM-79 IES Testing Available (Lighting Facts Partner)

# ELECTRICAL information

LipLite is a 12VDC (LEDs) or 12VAC (Incandescent) system that can carry up to 180(12V) Watts in a single run (15 amp - 14 gauge wire). LipLite requires a transformer/driver to operate. Our standard transformer's primary side voltage are 120 or 277 Volts. Consult factory for other voltages.

#### CALIFORNIA ACCENT LIGHTING, INC.

## APPLICATION information

LipLite Series is available with long life, energy efficient LEDs that allow for low maintenance installations. LipLite can be field cut for easy and fast installation not requiring exact field dimensions. LiptLite's flexibility allows for radius installations.

LipLite is excellent to illuminate areas for cove lighting, accent lighting, and other indirect applications. LipLite creates a warm, pleasant environment in restaurant interiors, office buildings, retail, and other venues.

### LM-79



Lighting Facts Partner - LM79 Testing Available ETL Listed - Dry or Wet Location

Meets UL and CSA Requirements



